
ReaSCAN: Compositional Reasoning in Language Grounding

Zhengxuan Wu*
Stanford University
wuzhengx@stanford.edu

Elisa Kreiss*
Stanford University
ekreiss@stanford.edu

Desmond C. Ong
National University of Singapore
dco@comp.nus.edu.sg

Christopher Potts
Stanford University
cgpotts@stanford.edu

Abstract

The ability to compositionally map language to referents, relations, and actions is an essential component of language understanding. The recent gSCAN dataset (Ruis et al. 2020, *NeurIPS*) is an inspiring attempt to assess the capacity of models to learn this kind of grounding in scenarios involving navigational instructions. However, we show that gSCAN’s highly constrained design means that it does not require compositional interpretation and that many details of its instructions and scenarios are not required for task success. To address these limitations, we propose **ReaSCAN**, a benchmark dataset that builds off gSCAN but requires compositional language interpretation and reasoning about entities and relations. We assess two models on ReaSCAN: a multi-modal baseline and a state-of-the-art graph convolutional neural model. These experiments show that ReaSCAN is substantially harder than gSCAN for both neural architectures. This suggests that ReaSCAN can serve as a valuable benchmark for advancing our understanding of models’ compositional generalization and reasoning capabilities.

1 Introduction

Natural languages are *compositional* [1, 2, 3] and *grounded* [4, 5, 6]; the meanings of complex phrases are derived from their parts, and meaning itself is defined by a mapping from language to referents, relations, and actions. It is therefore vital that we push NLP systems to be grounded and compositional as well. However, the major benchmarks in the field right now mostly do not support rich grounding, and it is often unclear whether they support learning compositional structures, as evidenced by their common failures at simple adversarial tests involving compositionality [7, 8, 9].

There are several benchmarks for testing compositional generalization [10, 11, 12, 13, 14]. SCAN [12] focuses on compositionality in the area of interpreting navigational instructions. Building off SCAN, Ruis et al. [14] propose a grounded version of SCAN called gSCAN, in which agents have to ground navigation commands in a grid world in order to identify the correct referent. gSCAN supports learning in idealized scenarios involving navigational instructions, and it seeks to probe for compositionality. The design is simple and flexible, making it a potentially valuable benchmark and a source for insights into how to design robust tests of language understanding.

However, we find that gSCAN has three major limitations: (1) its set of instructions is so constrained that preserving the linguistic structure of the command is not required; (2) the distractor objects in its

*Equal contribution.




Figure 1: Four command-world pairs for different command patterns. Our simple command is equivalent to gSCAN [14]. RD means distractors are randomly sampled. Referent targets shaded in red with distractors are shaded in blue, and are highlighted by green dash lines.

grounded scenarios are mostly not relevant for accurate understanding; and (3) in many examples, not all modifiers in the command are required for successful navigation, which further erodes the need for compositional interpretation and inflates model performance scores.

To address these limitations, we propose **ReaSCAN**, a benchmark dataset that builds off gSCAN and addresses its limitations. Figure 1 provides examples and a comparison with gSCAN. We establish that ReaSCAN requires both compositional language interpretation and complex reasoning about entities and relations. Like gSCAN, ReaSCAN is algorithmically generated, which allows us to vary the difficulty of the learning problems we pose and thus diagnose model limitations with precision. In addition, we introduce a range of complex distractor sampling strategies which, in case of incorrect target identification, can help pinpoint which failure in command understanding led to the error. This allows us to show that challenging distractors can severely impact performance in this task.

We assess two models on ReaSCAN: a multi-modal baseline and a state-of-the-art graph convolutional neural model. These experiments show that ReaSCAN is substantially harder than gSCAN for both neural architectures, and they verify that we can modify the difficulty of learning tasks in the desired ways to achieve fine-grained insights into model performance and model limitations. This suggests that ReaSCAN can serve as a valuable benchmark for advancing our understanding of models’ compositional generalization and reasoning capabilities in linguistic tasks. We hope also that the general techniques used to move from gSCAN to ReaSCAN can be applied more generally in the design of future benchmarks for assessing grounded, compositional language use.

2 Related Work

There are a variety of efforts underway to more deeply understand how neural models ground linguistic cues with visual inputs, including visual question answering [10, 15, 16, 17, 18], image captioning [19, 20, 21], referring expression resolution [12, 14], navigation [22, 23, 24] and program induction and synthesis [25, 26, 27]. Similar to previous synthetic benchmarks, our work aims to provide a controlled environment that can be used to evaluate a neural model’s generalization capabilities according to a variety of specific generalization tasks. Specifically, we focus on evaluating compositional generalization with referring expression resolution.

A number of recent approaches involve generating synthetic datasets to evaluate compositional generalization of neural models [10, 11, 13, 28, 29, 30, 31, 32]. For instance, [31] proposed CLOSURE, a set of unseen testing splits for the CLEVR dataset [10] which contains synthetically generated natural-looking questions about 3D geometric objects. Our work investigates a similar generalization over grounded linguistic inputs in a visual scene but focuses specifically on a model’s capability to resolve linguistic compositionality. We evaluate the generalization capabilities of neural models by testing them against unseen compositions of the language input which require grounding in simulated shape worlds.

Models performing well on gSCAN are a promising first test case for ReaSCAN. Numerous approaches have been proposed to handle at least some of the challenges posed by SCAN and gSCAN datasets including novel data augmentation methods and neural architectures [33, 34, 35, 36, 37, 38]. Successful neural models on gSCAN involve compositional neural networks which increase generalizability [37] and language conditioned graph neural networks for encoding objects [38]. While these techniques solve some of the simpler splits in gSCAN involving generalization of novel object attributes [38], we show that they are still ineffective for similar splits of ReaSCAN in Section 6.2. ReaSCAN, therefore, provides a more challenging benchmark, revealing clear shortcomings of current models’ generalization capabilities.

3 Background: The Grounded SCAN Benchmark (gSCAN)

The gSCAN benchmark is an extension of the SCAN dataset [12] with a focus on grounding actions in a changeable environment. In gSCAN, a grid world containing an agent and several shapes is paired with a command, such as “walk to the red square cautiously”. The goal is to generate an action sequence like `<left,right,right,left>` that lets the agent execute the command in that particular world to reach the referent target. Adverbs like “cautiously” assign specific modes of movement to the overall sequence. gSCAN enables tests for compositional generalization by presenting the model with unseen verb–adverb combinations (“walk cautiously” vs. “push cautiously”), unseen adjective–noun compositions, unseen color–shape feature co-occurrences on objects, and unseen locations for the target referent.

The guiding ideas behind gSCAN seem powerful and relevant, but we identify four ways in which specific design choices reduce the potential of the dataset to achieve its central goals:

1. Irrelevance of Word Order Since gSCAN is meant to be a simple synthetic dataset, all commands consist of a verb, a noun phrase consisting of a noun with a potential color and/or size modifier, and an optional adverb. Given this template, the word order of the input command is irrelevant for determining the correct action sequence. The words “walk to the red square cautiously” can be scrambled and still yield a unique correct order with only a single potential referent. Consequently, Bag-of-Words accounts are in principle sufficient for encoding the gSCAN commands. As a point of contrast, the commands in the earlier SCAN dataset, such as “walk twice and jump thrice”, cannot be scrambled in this way without a task-relevant loss of information, and are therefore much more challenging to solve on the command level.

2. A Limited Test for Linguistic Compositionality gSCAN includes a test set in which all commands involve a previously unseen referring expression combination (the novel NP “yellow square”), with the goal of seeing whether models can predict the meaning of the whole from its parts “yellow” and “square”, which are seen in training. This is a clear test for compositionality. However, unfortunately, the split creation process didn’t inherently require an understanding of “yellow” and “square” to be necessary for a unique identification in a specific world. In the split provided by the authors,¹ both the color and shape feature are only required in 62.7% of all test examples. (Color is sufficient in 25.2% of all test examples, shape in 10.6%, and either of the two in 1.4% of all cases.) gSCAN also includes a test split designed to require feature attribute composition: in training, the referent target is never an object with the color feature *red* and shape feature *square*. At test time, only red squares are targets and are referred to with all valid referring expressions (i.e., “(small|big)? red? square”). As in the previous split, color and shape feature in the command are necessary in just 62.5% of all test examples, making it equally unsuitable for investigating linguistic compositionality.

3. Biased Distractor Sampling Distractor sampling in gSCAN relies on random selection of all objects that are not mentioned in the command. In general, if the utterance mentions a blue circle, the algorithm creates all possible objects that aren’t blue circles. Then, it selects half of them as distractors. There is one exception: if the utterance contains a size modifier (as in “small blue circle”), there will be a big blue circle as a distractor. Due to the distractor sampling design, simple utterances such as “the circle” will only have one distractor, while more complex utterances will have many more. This makes by-chance accuracy dependent on the informativity/complexity of the linguistic expression.

¹<https://github.com/LauraRuis/groundedSCAN>

117 **4. Too Few Effective Distractors** As shown in the first example for gSCAN of Figure 1, the output
 118 action sequence stays the same even if we randomly reorder all objects except the referent target.
 119 In fact, the size, color, and shape of other objects can be modified without any effect on the output
 120 action sequence. As a result, grounding is based on essentially two objects, the two red circles. (See
 121 Section 4.2 for details about how distractors affect performance.)

122 In sum, gSCAN provides novel systematic ways of investigating grounded language understanding
 123 but it lacks a way to keep investigating the syntactic compositional questions in the command which
 124 motivated SCAN. ReaSCAN introduces more complex command structure that enforces models to
 125 retain some linguistic structure to solve it, and contains compositional splits that ensure the necessity
 126 of compositional generalization capabilities for the input command. Due to the more complex
 127 command structure, this requires elaborate distractor sampling strategies with the goal to make
 128 distractors maximally competitive to promote grounding to multiple objects in the world.

129 **4 The Reasoning-based SCAN Benchmark (ReaSCAN)**

130 We now introduce ReaSCAN, which seeks to address the above limitations of gSCAN. Like gSCAN,
 131 ReaSCAN is a command-based navigation task that is grounded in a grid world containing the agent,
 132 a referent target, and a set of distractors, as shown in Figure 1.

133 Given a command \mathbf{C}_i paired with a corresponding grid world $\mathcal{W}_{i,j}$, the goal is to generate an action
 134 sequence $\mathbf{a}_{i,j}$ which contains the actions that the agent needs to take in order to reach the target
 135 referent and operate on it. An oracle model learns a mapping \mathcal{G} that formulates $\mathbf{a}_{i,j} = \mathcal{G}(\mathcal{W}_{i,j}, \mathbf{C}_i)$
 136 for $i \in [1, N]$ where N is the number of commands and $j \in [1, M]$ where M is the number of worlds
 137 generated for each command.

138 Crucially, ReaSCAN extends gSCAN while ensuring two main desiderata: (1) word-order permu-
 139 tations in the command will lead to ambiguities about the intended referent, requiring a model to
 140 resolve linguistic structure, and (2) the identity of the referent depends on reasoning about multiple
 141 distractor objects in the world. Consider the 2-relative-clauses example (third from left) in
 142 Figure 1. If we scramble the word order of the command by swapping attributes between the second
 143 and the third objects, and change them to “small blue circle” and “red cylinder”, the referent target
 144 changes (e.g., object D1 in the world); additionally, if the model only understands the first relational
 145 clause “the same column as a blue cylinder”, it may discover multiple referent targets (e.g., object
 146 D2-1 in the world). These modifications ensure that understanding ReaSCAN commands requires
 147 resolving the syntactic structure of the command, while largely maintaining the simplicity of SCAN
 148 and gSCAN.

149 In the following sections, we discuss the key components of ReaSCAN. We first introduce the
 150 process of generating ReaSCAN commands. Next, we describe how commands are grounded with
 151 shape worlds, and specifically the distractor sampling strategies. Finally, we propose test splits
 152 which provide systematic tests of a model’s generalization abilities². Note that we discuss potential
 153 ReaSCAN artifacts in Appendix B.

154 **4.1 ReaSCAN Command Generation**

155 ReaSCAN commands are constructed with the following regular expression pattern:

Pattern := \$VV \$OBJ (that is \$REL_CLAUSE (and \$REL_CLAUSE)*)* \$ADV?

156 where the recursive structure allows commands to contain multiple relative clauses and conjunctive
 157 clauses. If there is no relative clause, the resulting commands are comparable to gSCAN commands
 158 (e.g., “walk to the red square cautiously”). From the regular expression, commands are created by
 159 sampling from the semantics of each primitive, which are terms starting with “\$” (Table 1). For
 160 example, we substitute \$REL \$OBJ for \$REL_CLAUSE, and we can further recursively sample each
 161 term from their assigned semantics.

162 During this process, we also introduce restrictions to avoid ungrammatical and unnatural commands,
 163 enforced by rule-based conditional sampling. This way, commands such as “walk to the square that

²We release the version of ReaSCAN used in this paper, and our code to generate ReaSCAN at <https://github.com/frankaging/Reason-SCAN>.

Syntax	Descriptions	Potential Meaning
\$VV	verb	{walk to, push, pull}
\$ADV	adverb	{while zigzagging, while spinning, cautiously, hesitantly}
\$SIZE	attribute	{small, big} [*]
\$COLOR	attribute	{red, green, blue, yellow}
\$SHAPE	attribute	{circle, square, cylinder, <i>box</i> , <i>object</i> }
\$OBJ	objects	(a the) \$SIZE? \$COLOR? \$SHAPE
\$REL	relations	{\$SameRow, \$SameCol, \$SameColor, \$SameShape, \$SameSize, \$IsInside}
\$REL_CLAUSE	clause	\$REL \$OBJ

Table 1: Definitions of syntax used in ReaSCAN command generation. ^{*}the actual size of any shape is chosen from {1,2,3,4} as in gSCAN [14].




Figure 2: Relations.

164 is in the same color as the red circle” would be excluded, as “walk to the red square” is a shorter and
 165 more direct formulation with the same meaning. See Appendix C for details about our rule-based
 166 conditional sampling over commands.

167 In this data creation procedure, both the relative clauses and conjunctive clauses have the flexibility
 168 to expand in depth and in width. In this paper, we focus on commands with a maximum of a single
 169 conjunction of two relative clauses. In total, we generate the following commands:

- 170 • Simple:= \$VV \$ADV? (equivalent to gSCAN commands)
- 171 • 1-relative-clause:= \$VV \$OBJ that is \$REL_CLAUSE \$ADV?
- 172 • 2-relative-clauses:= \$VV \$OBJ that is \$REL_CLAUSE and \$REL_CLAUSE \$ADV?

173 We use our framework to generate three separate subsets for each command pattern. We then define
 174 random train/dev/test splits for each of the subsets to benchmark difficulty (see Section 6.1 for details),
 175 where Simple commands are equivalent to gSCAN commands. As shown in Figure 4, the action
 176 sequence length has the same distribution as gSCAN and across all patterns. As a result, ReaSCAN
 177 does not require models to predict longer sequences, which would raise separate issues concerning
 178 generalization [39].

179 4.2 ReaSCAN World Generation with Active Distractor Sampling

180 Similar to gSCAN, we use the open-sourced MiniGym from Open-AI³ to generate multiple shape
 181 worlds for each command. Objects are freely placed in an $n \times n$ grid-world, where we fix $n = 6$.
 182 Given a command C_i , objects and their locations are determined as follows: (1) We select objects
 183 mentioned in C_i , initialize them with their specified features, and randomly fill underspecified features.
 184 For instance, in Figure 3, the command requires the second object to be green and a circle, but its
 185 size is not specified and so is randomly assigned (e.g., here as *big*). (2) The objects are randomly
 186 placed on the grid while ensuring the relations expressed in C_i are true. (3) We sample distractors in
 187 a way that ensures that failure to fully understand C_i has a high likelihood of leading to an incorrect
 188 prediction about the target.

189 As discussed in Section 3, careful distractor sampling is essential for ensuring that our dataset can be
 190 used to assess systems for compositionality. Distractors must reliably introduce uncertainty about the
 191 identity of the target.

192 For example, if the target is a small red circle, a large red circle competes with the target in the size
 193 dimension, and confusing the distractor with the target would indicate a lack of understanding of the
 194 size domain or its composition. Distractors that have little in common with the target are therefore
 195 weak distractors. We employ four distractor-sampling methods that ensure a challenging task that can

³<https://github.com/maximecb/gym-minigrid>




Figure 3: Illustration of the conversions between the multi-edge graph and the shape world or the command.




Figure 4: Length distributions of action sequences for different datasets.

be used to reliably diagnose specific model shortcomings. We exemplify their purpose by referring back to the 2-relative-clauses example (i.e., the third example) in Figure 1.

Attribute-based distractors compete with the target if a model struggles with size, color, and shape features. They are created by simulating a change of one of these features in the command and adding objects to the world which make a distractor the plausible target. For instance, if we substitute the shape attribute of the “blue cylinder” to “circle” in the command, the referent target changes (e.g., object D3 in the world). Correctly interpreting the shape attribute becomes crucial for correct target identification.

Isomorphism-based distractors become potential targets after word-order permutations of the command. For instance, if we scramble the word order of the command by swapping attributes between the second and the third objects, and change them to “small blue circle” and “red cylinder”, the referent target changes (e.g., object D1 in the world). These distractors are crucial to ensure the necessity of linguistic compositionality to solve the task while Bag-of-Words models can maximally achieve chance accuracy.

Relation-based distractors ensure that the relative clauses in the command are required to identify the intended target referent. For instance, if the model only understands the first relational clause “the same column as a blue cylinder”, other distractors may become the referent target (e.g., object D2-1 in the world); similarly, if the model only understands the second relational clause “the same row as a small red circle”, object D2-2 in the world may become the referent target.

For each world, we sample relation-based distractors exhaustively, and we sample at least one attribute-based distractor by randomly selecting one object and perturbing its attribute. For isomorphism-based distractors, we randomly select any pair of objects and swap attributes if applicable. If a distractor-sampling method cannot work for a specific command-world pair, we incorporate **random distractors** by randomly sampling a size, color and shape for each random distractor. This results in a maximum of 16 objects in each generated world. (For gSCAN, the maximum is 12.)

For size, a relative scalar adjective, we added an additional constraint. If the command contains a size modifier, a world always contains a distractor of a different size (similarly to gSCAN). To avoid vagueness about the intended referents, we ensure that there are only two sizes in that particular world. As the complexity of distractors increases, there is an increased probability that there could be more than one object in the world that could be the target referent. To ensure a unique solution for all examples, we develop graph-based representations (see Figure 3 for an example) of our shape worlds and use sub-graph matching algorithms to validate examples (see Appendix D for details).

4.3 Compositional Splits

ReaSCAN allows us to define a variety of different train/dev/test splits that vary in complexity. Table 3 provides an overview of the splits that we have explored to date. Test splits from category A investigate novel attribute compositions at the command and object level (see Section 6.2), which are adapted from gSCAN. Test splits in category B investigate how a model generalizes to previously

	Command-World Pairs			Random		Exact Match% (Std.)		GCN-LSTM	
	Train	Dev	Test	Dev	Test	M-LSTM		Dev	Test
						Dev	Test		
gSCAN	367,933	19,282	3,716	-	-	-	97.69 (0.22)	-	98.60 (0.95)
Simple	113,967	6,318	1,215	0.17 (0.06)	0.11 (0.13)	93.39 (1.97)	93.64 (2.52)	98.06 (0.98)	97.86 (1.27)
1-relative-clause	340,985	18,903	3,635	0.14 (0.04)	0.12 (0.02)	60.68 (3.04)	61.28 (1.81)	97.25 (0.68)	97.19 (0.79)
2-relative-clauses	549,634	30,470	5,859	0.12 (0.01)	0.13 (0.03)	53.08 (13.9)	52.77 (14.6)	96.80 (0.82)	96.85 (0.75)
2-relative-clauses (RD)	569,835	31,590	6,075	0.16 (0.02)	0.12 (0.05)	89.56 (0.66)	89.81 (0.60)	98.14 (0.45)	97.97 (0.48)
All	539,722	29,920	5,753	0.13 (0.02)	0.14 (0.03)	78.48 (1.38)	79.04 (1.24)	98.78 (0.55)	98.96 (0.59)

Table 2: ReaSCAN statistics with random splits and performance results of baseline models trained separately for each command pattern. All excludes compositional splits. Results are aggregated from 3 independent runs with different random seeds. Performance with gSCAN is from original papers for M-LSTM [14] and GCN-LSTM [38].

unseen co-occurrences of concepts including both objects and relations (see Section 6.3), unique to ReaSCAN. Finally, category C investigates if a model can extrapolate from simple to more complex embedded phrase structures (see Section 6.4).⁴

5 Models

We report ReaSCAN experiments with three models. We give high-level descriptions here, and Appendix E provides additional details.

Random Baseline A sequence-generation model that randomly samples actions from our vocabulary and generates action sequences with the same lengths as the actual action sequences. This serves as the lower bound of model performance.

M-LSTM A multimodal LSTM model, which we adapted from a model proposed for gSCAN [14]. This is a sequence-to-sequence (seq2seq) model [40] that takes an encoding of the visual input as a separate modality. The encoder consists of two parts: a bidirectional LSTM (BiLSTM; [41, 42]) as the language encoder for the commands, and a convolutional network (CNN) [43] as the shape-world encoder. Given a world-command pair $(\mathcal{W}_{i,j}, \mathbf{C}_i)$ as the input, the goal is to generate an action sequence $\mathbf{a}_{i,j}$. The output sequence is generated by an attention-based bidirectional LSTM.

GCN-LSTM A graph convolutional neural (GCN) network with a multimodal LSTM which is, to the best of our knowledge, the best-performing model on gSCAN [38]. The model encodes commands using a BiLSTM with multi-step textual attention [44]. The shape world is encoded using a GCN layer. The command embedding is fed into the GCN which makes it language-conditioned. Each node in GCN is initialized as object representation provided in the dataset. Then, it performs multi-rounds message passing to contextualize object embeddings based on relations. Then, the object embeddings are fed through another CNN layer before feeding into an attention-based BiLSTM together with the command embedding to generate the output sequence, as in Ruis et al. [14].

6 Experiments

6.1 Random Split

We generate large random splits for all patterns to validate that models can learn to follow ReaSCAN commands when there are no systematic differences between training and test. We do this while systematically varying the complexity of the inputs, from Simple (no relative clauses, as in gSCAN) to 2-relative-clauses, and we evaluate when merging all three together (All). Appendix A provides additional details concerning how these splits are created.

The results in Table 2 show that the GCN-LSTM is uniformly superior to the M-LSTM. In addition, for both models, performance drops as the number of relative clauses grows. The M-LSTM performs far

⁴We deliberately skip adapting some splits from gSCAN, such as novel relative agent positions, novel action length, and novel adverbs, since SCAN and gSCAN are sufficient for their evaluation. However, ReaSCAN is easily adaptable to these cases, as well.

Compositional Splits	Command-World Pairs	Exact Match% (Std.)		
		Random	M-LSTM	GCN-LSTM
Simple (Test)	921	0.07 (0.06)	96.27 (0.54)	99.71 (0.22)
1-relative-clause (Test)	2,120	0.08 (0.07)	79.09 (2.63)	99.14 (0.23)
2-relative-clauses (Test)	2,712	0.10 (0.02)	73.16 (1.85)	98.58 (0.54)
All (Test)	5,753	0.14 (0.03)	79.04 (1.24)	98.96 (0.59)
A1:novel color modifier	22,057	0.12 (0.05)	50.36 (4.03)	92.25 (0.77)
A2:novel color attribute	81,349	0.14 (0.01)	14.65 (0.55)	42.05 (4.55)
A3:novel size modifier	35,675	0.14 (0.03)	50.98 (3.69)	87.46 (2.22)
B1:novel co-occurrence of objects	10,002	0.12 (0.03)	52.17 (1.63)	69.74 (0.30)
B2:novel co-occurrence of relations	6,660	0.16 (0.05)	39.41 (1.53)	52.80 (2.75)
C1:novel conjunctive clause length	8,375	0.10 (0.01)	49.68 (2.73)	57.01 (7.99)
C2:novel relative clauses	8,003	0.09 (0.02)	25.74 (1.36)	22.07 (2.66)

Table 3: ReaSCAN statistics with compositional splits and performance results of baseline models trained with all command patterns. Results are aggregated from 3 independent runs with different random seeds.

worse with longer clauses (43.65% drop from Simple to 2-relative-clauses). The GCN-LSTM experiences smaller drops (1.03% from Simple to 2-relative-clauses). These results suggest that graph-based neural networks may be better at capturing relations between objects and reasoning over relations than the plain CNNs used by the M-LSTM. Additionally, the GCN-LSTM shows smaller standard deviations from random initializations, suggesting it is more robust on the ReaSCAN task as well.

When we resample shape worlds with only random distractors, performance from both models increases. In fact, with random distractors, test performance of 2-relative-clauses drops less than 4% compared to the Simple conditions, for both models. This finding reinforces the importance of sampling challenging distractors.

6.2 A: Novel Object Attributes

Evaluating neural models on unseen combinations of object attributes remains an ongoing challenge [10, 11, 45]. Here, we extend gSCAN’s efforts in this area by testing models on unseen composites of size, color, and shape.

A1: Novel Color Modifier In this split, we hold out all examples where the commands contain “yellow square” for any size (e.g., “small yellow square” or “big yellow square”), meaning that models cannot ground any targets to the expression containing “yellow square”. However, the train set includes examples with phrases such as “yellow cylinder” (52,820 unique examples) and “blue square” (90,693 unique examples). At test time, models need to zero-shot generalize in order to interpret “yellow square” correctly. Our distractor sampling strategy ensures that the scenario contains relevant non-yellow squares and non-square yellow things, so that both shape and color information needs to be integrated for correct target identification. Table 3 shows that both models perform worse on these splits than with random splits, with the M-LSTM showing the largest drop in performance. While the GCN-LSTM is clearly getting traction on this task, the results show that compositional generalization remains a serious challenge.

A2: Novel Color Attribute In this split, we test model performance on a novel combination of the target referent’s visual features. To test that, we ensure that red squares are never targets during training. Commands also never contain “red square” even in the position of the relations (i.e., inside the relative clauses). However, differently sized red squares are seen during training since they often appear as non-target background objects (266,164 unique examples). We make sure the color attribute is necessary for identifying the target referent, and restrictions apply to objects at all positions in the command. Our results in Table 3 show that this split is slightly harder for both models (with a 81.47% drops for M-LSTM and a 57.51% for GCN-LSTM) than A1 as models need to learn visual composites of “red square” from potential reasoning over background objects. Once again, our results suggest that GCN-LSTM is better at generalizing to unseen compositions.

A3: Novel Size Modifier Size is a relative concept in our commands; the same object could be a small square in one context and not in another, depending on the sizes of the other squares present. Similar to A1, we evaluate whether models can zero-shot generalize to new size/shape combinations. Specifically, we hold out all commands containing “small cylinder”, meaning that models have not seen expressions such as “small cylinder” or “small yellow cylinder” during training. At test time, models need to generalize when a small cylinder in any color is referred to with expressions such as “small cylinder”. During training, the models still learn the relative meaning of “small” by seeing examples containing expressions such as “small square” (22,866 unique examples) or “small red circle” (23,838 unique examples). In addition to generalizing over new composites, models also cannot simply memorize “small” as a specific size (e.g., object of size 2), since the meaning is contextually determined. Similar to A1, we ensure that the size attribute is necessary for identifying the referent target, and restrictions apply to objects at all positions.

Table 3 shows that both models achieve comparable performance to A1 which suggests that the generalization capabilities across unseen color and size composites for both models are similar. GCN-LSTM continues to perform better than M-LSTM suggesting that GCN is more successful in generalizing to relative concept as well.

6.3 B: Novel Co-occurrence of Concepts

In this experimental condition, we assess the ability of models to generalize to novel combinations of concepts including objects and relations at the clause level.

B1: Novel Co-occurrence of Objects To construct this split, we first collect all objects (e.g., “small red circle” and “big blue square”) mentioned in the training set. Then, we construct commands with seen objects that never co-occur during training. Additionally, we control commands to only contain co-occurrences of relations that are seen during training. In this condition, the GCN-LSTM continues to outperform the M-LSTM in generalizing to unseen co-occurrences of relations. Compared to novel attribute modifiers (i.e., A1 and A3), GCN-LSTM performance decreases.

B2: Novel Co-occurrence of Relations In this split, we hold out examples containing commands mentioning both “same size as” and “inside of” relations, meaning the models never see examples such as “walk to the object that is the same shape as the red object and that is inside of the red box”. However, in training, models see cases where the relation “inside of” co-occurs with other relations, such as “same row as” (58,863 unique examples). Table 3 shows that both models perform worse compared to B1. This suggests that generalizing over co-occurrence of relations is harder for both model architectures which requires novel reasoning over objects.

6.4 C: Novel Phrase Structures

As shown in Section 4.1, the number of phrase structures in ReaSCAN can be manipulated. In the following experiments, we test whether a model trained with at most two relative clauses (see Section 4.1 for all patterns) can generalize well to commands with novel phrase structures.

C1: Novel Conjunctive Clause Length In the first experiment, we generate examples with commands that have one additional conjunction clause (i.e., “and \$REL_CLAUSE” is added to the 2-relative-clauses commands). Our results in Table 3 suggest that both models fail to generalize over longer relative clauses (with a 37.15% drop for M-LSTM and a 42.39% drop for GCN-LSTM). Since both models are LSTM-based, it may suggest that LSTM-based models don’t generalize well to longer sequences at test time, which has been found in more recent studies [12], though some of this may trace to how stop tokens are used [39].

C2: Novel Relative Clauses In this experiment, we generate examples with commands that have two recursive relative clauses (i.e., “and” is swapped with “that is” in the 2-relative-clauses commands)⁵. For this condition, both models result in catastrophic failures (with a 67.43% drop for M-LSTM and a 77.70% drop for GCN-LSTM). Our results suggest that GCN is incapable of generalizing over novel recursive relations. The performance degradation of GCN-LSTM may suggest that the fault

⁵We only allow relations to be “same row as” and “same column as” to avoid invalid commands.

lies with the way the GCN component embeds relational information in its object representations. This is a strength for known combinations but a potential hindrance for novel ones.

7 Conclusion

We introduced the ReaSCAN benchmark, which seeks to build on the insights behind the gSCAN dataset of Ruis et al. [14] while addressing its shortcomings. ReaSCAN is designed to support controlled assessments of whether models have truly learned grounded, compositional semantics. We find that a state-of-the-art GCN-LSTM model achieves strong results for most of the compositional splits from gSCAN. Results on ReaSCAN, however, suggest that those capabilities are overestimates. Furthermore, ReaSCAN allows for more intricate investigations of the resolution of linguistic structure. The GCN-LSTM model is successful at tasks involving novel linguistic modifiers and novel entity attribute combinations, but it fails to generalize in settings involving novel relation combinations and longer commands. These results indicate that, while we are making progress in achieving grounded, compositional models, many substantial challenges remain. While ReaSCAN introduces complexity to the problem due to sophisticated distractor sampling strategies and more elaborate input commands, the synthetic nature of the dataset remains far from complex naturalistic data. We hope to see ReaSCAN starting to bridge this gap, e.g., by extending it with human annotations.

Broader Impact

Enabling neural models to compositionally generalize learnt knowledge to unseen situations mimics how humans use and understand language. Advancing benchmarks to evaluate models with such abilities becomes increasingly important. Our ReaSCAN benchmark is designed to advance our understandings of models’ compositional generalization and reasoning capabilities. We hope ReaSCAN could serve as a valuable benchmark dataset to propel new neural models that think, reason and act like humans. We do not foresee any negative impact on society or our research community.

References

- [1] Richard Montague. *Formal Philosophy: Selected Papers of Richard Montague*. Yale University Press, New Haven, CT, 1974.
- [2] Barbara H. Partee. Compositionality. In Fred Landman and Frank Veltman, editors, *Varieties of Formal Semantics*, pages 281–311. Foris, Dordrecht, 1984. Reprinted in Barbara H. Partee (2004) *Compositionality in formal semantics*, Oxford: Blackwell 153–181. Page references to the reprinting.
- [3] Theo M. V. Janssen. Compositionality. In Johan van Benthem and Alice ter Meulen, editors, *Handbook of Logic and Language*, pages 417–473. MIT Press and North-Holland, Cambridge, MA and Amsterdam, 1997.
- [4] Herbert H. Clark. *Using Language*. Cambridge University Press, Cambridge, 1996.
- [5] Prashant Parikh. *The Use of Language*. CSLI, Stanford, CA, 2001.
- [6] Stevan Harnad. The symbol grounding problem. *Physica D: Nonlinear Phenomena*, 42(1-3):335–346, 1990.
- [7] Max Glockner, Vered Shwartz, and Yoav Goldberg. Breaking NLI systems with sentences that require simple lexical inferences. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 650–655, Melbourne, Australia, July 2018. Association for Computational Linguistics. doi: 10.18653/v1/P18-2103. URL <https://www.aclweb.org/anthology/P18-2103>.
- [8] Aakanksha Naik, Abhilasha Ravichander, Norman Sadeh, Carolyn Rose, and Graham Neubig. Stress test evaluation for natural language inference. In *Proceedings of the 27th International Conference on Computational Linguistics*, pages 2340–2353, Santa Fe, New Mexico, USA, August 2018. Association for Computational Linguistics. URL <https://www.aclweb.org/anthology/C18-1198>.
- [9] Yixin Nie, Yicheng Wang, and Mohit Bansal. Analyzing compositionality-sensitivity of NLI models. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 6867–6874, 2019.

- [10] Justin Johnson, Bharath Hariharan, Laurens Van Der Maaten, Li Fei-Fei, C Lawrence Zitnick, and Ross Girshick. Clevr: A diagnostic dataset for compositional language and elementary visual reasoning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 2901–2910, 2017.
- [11] Felix Hill, Karl Moritz Hermann, Phil Blunsom, and Stephen Clark. Understanding grounded language learning agents. 2018.
- [12] Brenden Lake and Marco Baroni. Generalization without systematicity: On the compositional skills of sequence-to-sequence recurrent networks. In *International Conference on Machine Learning*, pages 2873–2882. PMLR, 2018.
- [13] Felix Hill, Andrew K Lampinen, Rosalia Schneider, Stephen Clark, Matthew Botvinick, James L McClelland, and Adam Santoro. Environmental drivers of systematicity and generalization in a situated agent. In *ICLR*, 2020.
- [14] Laura Ruis, Jacob Andreas, Marco Baroni, Diane Bouchacourt, and Brenden M Lake. A benchmark for systematic generalization in grounded language understanding. *Advances in Neural Information Processing Systems*, 33, 2020.
- [15] Kexin Yi, Chuang Gan, Yunzhu Li, Pushmeet Kohli, Jiajun Wu, Antonio Torralba, and Joshua B Tenenbaum. Clevrer: Collision events for video representation and reasoning. In *International Conference on Learning Representations*, 2019.
- [16] Ramakrishna Vedantam, Arthur Szlam, Maximilian Nickel, Ari Morcos, and Brenden Lake. Curi: A benchmark for productive concept learning under uncertainty. *arXiv preprint arXiv:2010.02855*, 2020.
- [17] Alane Suhr, Mike Lewis, James Yeh, and Yoav Artzi. A corpus of natural language for visual reasoning. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 217–223, 2017.
- [18] Drew A Hudson and Christopher D Manning. Gqa: A new dataset for real-world visual reasoning and compositional question answering. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 6700–6709, 2019.
- [19] Junhua Mao, Jonathan Huang, Alexander Toshev, Oana Camburu, Alan L Yuille, and Kevin Murphy. Generation and comprehension of unambiguous object descriptions. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 11–20, 2016.
- [20] Ramakrishna Vedantam, Samy Bengio, Kevin Murphy, Devi Parikh, and Gal Chechik. Context-aware captions from context-agnostic supervision. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 251–260, 2017.
- [21] Richang Hong, Daqing Liu, Xiaoyu Mo, Xiangnan He, and Hanwang Zhang. Learning to compose and reason with language tree structures for visual grounding. *IEEE transactions on pattern analysis and machine intelligence*, 2019.
- [22] Peter Anderson, Qi Wu, Damien Teney, Jake Bruce, Mark Johnson, Niko Sünderhauf, Ian Reid, Stephen Gould, and Anton Van Den Hengel. Vision-and-language navigation: Interpreting visually-grounded navigation instructions in real environments. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3674–3683, 2018.
- [23] Fengda Zhu, Yi Zhu, Xiaojun Chang, and Xiaodan Liang. Vision-language navigation with self-supervised auxiliary reasoning tasks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10012–10022, 2020.
- [24] Jesse Thomason, Michael Murray, Maya Cakmak, and Luke Zettlemoyer. Vision-and-dialog navigation. In *Conference on Robot Learning (CoRL)*, 2019.
- [25] Chi Zhang, Feng Gao, Baoxiong Jia, Yixin Zhu, and Song-Chun Zhu. Raven: A dataset for relational and analogical visual reasoning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 5317–5327, 2019.
- [26] Kevin Ellis, Catherine Wong, Maxwell Nye, Mathias Sable-Meyer, Luc Cary, Lucas Morales, Luke Hewitt, Armando Solar-Lezama, and Joshua B Tenenbaum. Dreamcoder: Growing generalizable, interpretable knowledge with wake-sleep bayesian program learning. *arXiv preprint arXiv:2006.08381*, 2020.

- [27] Weili Nie, Zhiding Yu, Lei Mao, Ankit B Patel, Yuke Zhu, and Anima Anandkumar. Bongard-logo: A new benchmark for human-level concept learning and reasoning. *Advances in Neural Information Processing Systems*, 33, 2020.
- [28] Samuel Bowman, Christopher Potts, and Christopher D Manning. Recursive neural networks can learn logical semantics. In *Proceedings of the 3rd workshop on continuous vector space models and their compositionality*, pages 12–21, 2015.
- [29] Justin Johnson, Bharath Hariharan, Laurens Van Der Maaten, Judy Hoffman, Li Fei-Fei, C Lawrence Zitnick, and Ross Girshick. Inferring and executing programs for visual reasoning. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 2989–2998, 2017.
- [30] Maxime Chevalier-Boisvert, Dzmitry Bahdanau, Salem Lahlou, Lucas Willems, Chitwan Saharia, Thien Huu Nguyen, and Yoshua Bengio. Babyai: A platform to study the sample efficiency of grounded language learning. *arXiv preprint arXiv:1810.08272*, 2018.
- [31] Dzmitry Bahdanau, Harm de Vries, Timothy J O’Donnell, Shikhar Murty, Philippe Beaudoin, Yoshua Bengio, and Aaron Courville. Closure: Assessing systematic generalization of clevr models. *arXiv preprint arXiv:1912.05783*, 2019.
- [32] Dzmitry Bahdanau, Shikhar Murty, Michael Noukhovitch, Thien Huu Nguyen, Harm de Vries, and Aaron Courville. Systematic generalization: what is required and can it be learned? *arXiv preprint arXiv:1811.12889*, 2018.
- [33] Jacob Andreas. Good-enough compositional data augmentation. *arXiv preprint arXiv:1904.09545*, 2019.
- [34] Brenden M Lake. Compositional generalization through meta sequence-to-sequence learning. *arXiv preprint arXiv:1906.05381*, 2019.
- [35] Maxwell I Nye, Armando Solar-Lezama, Joshua B Tenenbaum, and Brenden M Lake. Learning compositional rules via neural program synthesis. *arXiv preprint arXiv:2003.05562*, 2020.
- [36] Xinyun Chen, Chen Liang, Adams Wei Yu, Dawn Song, and Denny Zhou. Compositional generalization via neural-symbolic stack machines. *arXiv preprint arXiv:2008.06662*, 2020.
- [37] Christina Heinze-Deml and Diane Bouchacourt. Think before you act: A simple baseline for compositional generalization. *arXiv preprint arXiv:2009.13962*, 2020.
- [38] Tong Gao, Qi Huang, and Raymond Mooney. Systematic generalization on gscan with language conditioned embedding. In *Proceedings of the 1st Conference of the Asia-Pacific Chapter of the Association for Computational Linguistics and the 10th International Joint Conference on Natural Language Processing*, pages 491–503, 2020.
- [39] Benjamin Newman, John Hewitt, Percy Liang, and Christopher D. Manning. The EOS decision and length extrapolation. In *Proceedings of the Third BlackboxNLP Workshop on Analyzing and Interpreting Neural Networks for NLP*, pages 276–291, Online, November 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.blackboxnlp-1.26. URL <https://www.aclweb.org/anthology/2020.blackboxnlp-1.26>.
- [40] Ilya Sutskever, Oriol Vinyals, and Quoc V Le. Sequence to sequence learning with neural networks. *Advances in Neural Information Processing Systems*, 27:3104–3112, 2014.
- [41] Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8):1735–1780, 1997.
- [42] Mike Schuster and Kuldip K Paliwal. Bidirectional recurrent neural networks. *IEEE transactions on Signal Processing*, 45(11):2673–2681, 1997.
- [43] Kuniyuki Fukushima and Sei Miyake. Neocognitron: A self-organizing neural network model for a mechanism of visual pattern recognition. In *Competition and cooperation in neural nets*, pages 267–285. Springer, 1982.
- [44] Drew A Hudson and Christopher D Manning. Compositional attention networks for machine reasoning. In *International Conference on Learning Representations*, 2018.
- [45] SM Ali Eslami, Danilo Jimenez Rezende, Frederic Besse, Fabio Viola, Ari S Morcos, Marta Garnelo, Avraham Ruderman, Andrei A Rusu, Ivo Danihelka, Karol Gregor, et al. Neural scene representation and rendering. *Science*, 360(6394):1204–1210, 2018.

- 496 [46] Luigi P Cordella, Pasquale Foggia, Carlo Sansone, and Mario Vento. A (sub) graph isomorphism algorithm
497 for matching large graphs. *IEEE transactions on pattern analysis and machine intelligence*, 26(10):
498 1367–1372, 2004.
- 499 [47] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *ICLR (Poster)*, 2015.
- 500 [48] François Chollet. On the measure of intelligence. *arXiv preprint arXiv:1911.01547*, 2019.

Checklist

1. For all authors...
 - (a) Do the main claims made in the abstract and introduction accurately reflect the paper’s contributions and scope? [\[Yes\]](#)
 - (b) Did you describe the limitations of your work? [\[Yes\]](#) See Appendix B.
 - (c) Did you discuss any potential negative societal impacts of your work? [\[N/A\]](#)
 - (d) Have you read the ethics review guidelines and ensured that your paper conforms to them? [\[Yes\]](#)
No human data is collected.
2. If you are including theoretical results...
 - (a) Did you state the full set of assumptions of all theoretical results? [\[N/A\]](#)
 - (b) Did you include complete proofs of all theoretical results? [\[N/A\]](#)
3. If you ran experiments...
 - (a) Did you include the code, data, and instructions needed to reproduce the main experimental results (either in the supplemental material or as a URL)? [\[Yes\]](#) See Section 4.
 - (b) Did you specify all the training details (e.g., data splits, hyperparameters, how they were chosen)? [\[Yes\]](#) See Section 4.
 - (c) Did you report error bars (e.g., with respect to the random seed after running experiments multiple times)? [\[Yes\]](#) See our main results in Table 2 and Table 3.
 - (d) Did you include the total amount of compute and the type of resources used (e.g., type of GPUs, internal cluster, or cloud provider)? [\[Yes\]](#) See Appendix A.
4. If you are using existing assets (e.g., code, data, models) or curating/releasing new assets...
 - (a) If your work uses existing assets, did you cite the creators? [\[Yes\]](#)
 - (b) Did you mention the license of the assets? [\[N/A\]](#) Unfortunately, the original authors (i.e., owner of the code bases) are not providing specific license. But they are public available, and people are citing and using their codes. We clearly cite and reference to their codes in our paper.
 - (c) Did you include any new assets either in the supplemental material or as a URL? [\[Yes\]](#)
 - (d) Did you discuss whether and how consent was obtained from people whose data you’re using/curating? [\[N/A\]](#) Synthetic dataset, not applicable.
 - (e) Did you discuss whether the data you are using/curating contains personally identifiable information or offensive content? [\[N/A\]](#) Synthetic dataset, not applicable.
5. If you used crowdsourcing or conducted research with human subjects...
 - (a) Did you include the full text of instructions given to participants and screenshots, if applicable? [\[N/A\]](#) Synthetic dataset, not applicable.
 - (b) Did you describe any potential participant risks, with links to Institutional Review Board (IRB) approvals, if applicable? [\[N/A\]](#) Synthetic dataset, not applicable.
 - (c) Did you include the estimated hourly wage paid to participants and the total amount spent on participant compensation? [\[N/A\]](#) Synthetic dataset, not applicable.

538 Appendix for ‘ReaSCAN: Compositional Reasoning in 539 Language Grounding’

540 A Dataset Generation

541 A.1 Action Sequence

542 Following gSCAN [14], ReaSCAN agents produce strings composed of action symbols {walk, push, pull,
543 stay, L_turn, R_turn}. The actions push and pull correspond to the “push” and “pull” verbs in the command.
544 For the verb “push”, the agent must push the referent object where pushing requires moving something as far as
545 possible before hitting a wall or another object. For the verb “pull”, the agent must pull the referent object, in
546 which case it would pull the object back as far as possible before hitting a wall or another object. Additionally,
547 any object of size 1 or 2 is labeled as *light*, and any object of size 3 or 4 is labeled as *heavy*. If the referent target
548 is a heavy object, the agent needs to push twice or pull twice to move to the next cell (e.g., ⟨push,push⟩ or
549 ⟨pull,pull⟩). The optional adverbs at the end of the command may alter action sequences by inserting actions
550 following the adverb. For example, a list of actions ⟨L_turn,L_turn,L_turn,L_turn⟩ is inserted into the
551 action sequence to fulfill the adverbial “while spinning”. Since composition generalization on adverbs is not the
552 focus of this paper, we randomly sample adverbs for each command. See the original gSCAN paper for details
553 on adverbs creation [14].

554 A.2 Grounded Determiners

555 ReaSCAN further extends the naturalness of the linguistic input by grounding its determiners. If an NP in the
556 command (e.g., “red circle”) is preceded by the definite determiner “the”, there is only one red circle in the
557 world. Otherwise, the object is preceded by the indefinite determiner “a”.

558 A.3 Dataset Statistics

559 Given the rich structure of our commands (see Section 4.1), the number of possible commands grows substantially
560 with longer patterns. To ensure we can still generate enough shape worlds per command, we have to down-
561 sample our commands significantly for longer commands. For the Simple command, we exhaustively collect
562 all commands, totalling 675 commands. For commands for one or more relative clauses, we then sample 2,025
563 commands for 1-relative-clause, and 3,375 for 2-relative-clauses. For each command, we sample
564 180 shape worlds, which is similar to the gSCAN setup. Our framework is also able to generate the full version
565 of ReaSCAN (i.e., considering all combinations of commands), which, though, uses about 250G of disk space.

566 A.4 Infrastructure Setups

567 To generate commands for all three patterns, it takes approximately 16 hours using a single process on a standard
568 CPU cluster. With 50 processes, it takes less than 20 minutes for the largest subset in this paper.

569 B Dataset Artifacts

570 In contrast to realistic datasets, synthetic datasets provide controllable environments for testing a specific aspect
571 of neural models. However, synthetic datasets may produce artifacts induced from the programs generating them.
572 Here, we disclose, as comprehensively as we can, potential artifacts resulting from our data generation process.

573 B.1 Non-comprehensive Linguistic Structures

574 As discussed in Section 4.1, commands from ReaSCAN follow a specific linguistic template and are non-
575 comprehensive in covering all linguistic structures. For examples, there is no confusion about where relative
576 clauses attach. Additionally, the location of occurrence of verbs and adverbs is fixed in our commands. In parallel,
577 we also down-sample our commands for the 1-relative-clause and 2-relative-clauses conditions, to
578 make ReaSCAN models trainable with reasonable computing resources.

579 B.2 Non-comprehensive Distractors

580 To generate a complete list of distractors for commands like “walk to the red circle that is in the same row as
581 the blue square”, we need to change each attribute (e.g., “red”, “circle”, “blue” and “square”) while holding
582 others constant. Consequently, our 2-relative-clauses commands could potentially require more than 600
583 distractors to fulfill a complete sampling of distractors. However, this leads to a dataset that is incomparable

584 to gSCAN, which samples at most 12 distractors. Thus, we randomly select a set of phrases and make them
585 necessary for each command (see Section 4.2 for details about distractor sampling strategies).

586 We quantify the percentages of different types of distractors appearing in ReaSCAN (see definitions in Sec-
587 tion 4.2 and Figure 5). Those quantifications are based on the distractors we explicitly generate to fulfill these
588 purpose, therefore serving as a lower-bound estimation for all effective distractors within a world. By chance,
589 some might in fact fulfill multiple purposes or a random distractor might by chance be highly competitive
590 with the target, resulting in a higher number of effective distractors. As shown in Figure 5, relation-based dis-
591 tractors are present in almost all examples with `1-relative-clause` and `2-relative-clauses` commands.
592 For `Simple` and `1-relative-clause`, we sample attribute-based distractors for almost all examples. For
593 `2-relative-clauses`, we only sample attribute-based distractors when applicable. For example, we skip
594 sampling attribute-based distractors when there are more than 2 boxes present in the shape world. As a result,
595 attribute-based distractors are present in about 60% of the examples for `2-relative-clauses` commands.
596 Random distractors are present in close to 100% of worlds for simpler commands (e.g., `Simple` commands), and
597 close to 0% of worlds for commands with more complex structures (e.g., `2-relative-clauses` commands).
598 Additionally, we only sample isomorphism-based distractors when applicable. For example, we only swap
599 attributes between objects that are not the referent target.

600 B.3 Shapes and Relations Biases

601 As discussed in Section 4.1 and Appendix C, we sample commands following a set of rules, which may lead
602 to imbalanced sampling for shapes and relations. For example, the shape “box” may only appear after the
603 relational clause “is inside of”. As a result, the frequencies of the shape “box” and the relational clause “is inside
604 of” are drastically different from the others. Additionally, we disallow unnatural commands such as “walk to
605 the red circle that is in the same color as the square” or “walk to the circle that is in the same color as the red
606 square”, where the relation is redundant or the unnatural command can be simplified. Following these rules, the
607 frequencies of different relations and attributes could be further stratified.

608 Figure 5 also includes frequency plots for different sizes, colors, shapes, and relations in ReaSCAN. We include
609 frequency distributions for the commands and the shape worlds separately. For colors, frequencies are evenly
610 distributed. For the sizes in commands (e.g., “big” or “small”), frequencies are evenly distributed. For the actual
611 sizes in specific shape worlds, smaller sizes have lower frequencies. This is an artifact due to the shape “box”.
612 Examples including larger boxes may tend to be valid examples compared to smaller ones, which impose spatial
613 limitations. For shapes except the box, frequencies are evenly distributed. Box is less frequent, as it can only
614 follow the specific relation “is inside of”. For selected relations, frequencies are extremely biased. As shown in
615 Figure 5, relations such as “same shape as”, “same color as”, and “same size as” are much less frequent than the
616 others. This is due to the fact that we exclude a significant number of unnatural commands that contain these
617 relations (see Appendix C for details).

618 B.4 Self-exclusiveness

619 We assume every object mentioned maps to a unique object in the generated world. For example, if the command
620 is “walk to the object that is in the same color as the square”, the target is not allowed to be the square itself.
621 This is generally not true in the real world.

622 B.5 Other Induced Artifacts

623 Figure 5 includes the distributions for verbs and adverbs presented in our commands. As shown in the plot, both
624 verbs and adverbs distribute uniformly. We also include distributions for agent-facing directions and agent–target
625 relative directions at the start. As in gSCAN [14], our agent always start facing east. Additionally, the relative
626 directions between the agent and the target at the start are distributed uniformly.

627 C Rule-based Command Samplings

628 As described in Section 4.1, our command generation process involves building relational clauses between
629 objects. To prevent generated commands from being ungrammatical, we enforce some explicit rules when
630 sampling commands:

- 631 • **Rule 1A:** When a “same shape as” relational clause is present in the command (e.g., “OBJ1 that is
632 in the same shape as OBJ2”), both objects for this clause cannot contain any shape descriptor. For
633 example, we consider “a red object that is in the same shape as a red square” as unnatural since one
634 could just say “a red square”. If OBJ1 contains a shape descriptor already, then the relational clause is
635 unnecessary.




Figure 5: Statistics of ReaSCAN.

- Rule 1B: When the “same color as” relational clause is present in the command, both objects for this clause cannot contain any color descriptor.
- Rule 1C: When the “same size as” relational clause is present in the command, both objects for this clause cannot contain any size descriptor. For size, we only allow two sizes for any objects when size descriptors are mentioned (e.g., a circle can only be in either of two random sizes if “small circle” appears in any command). This way there is never a small, big and medium-sized circle in a particular world where the size modifier could be confusing.
- Rule 2: The following shape of the “is inside of” relational clause must be a box.
- Rule 3: For any object term that has relational clauses following it, it cannot be over-specified with descriptors. For example, if we have “OBJ1 that is in the same shape as OBJ2”, we only allow relational conjunction clauses other than “same shape as”.
- Rule 4: In contrast to gSCAN [14], we enforce an order of modifiers where size descriptors proceed color descriptors (e.g., we allow “small red circle” but not “red small circle”).

These rules may over-sample or down-sample certain relations and shapes. We discuss these potential artifacts results in Section B.

D Sub-graph Matching

D.1 Multi-edge Graph Representation

Our distractor sampling strategies incentivize models to learn compositional reasoning. At the same time, these strategies increase the chance that the referent target becomes unidentifiable. For example, even if we randomly place objects in a world, they may form relations consistent with the command by chance. We address this issue by solving constraints using a graph representation.

We represent each world as a graph where nodes represent objects and edges represent relations between objects (see Figure 3 for an example). Each node has attribute-based relations with other nodes. For example, a “red circle” node will have a SAME_COLOR edge to a “red square” node. To make sure the referent target is unique for every command–world pair, we ensure only one referent target can be identified by querying the graph with our command. We simplify this problem as a problem of sub-graph matching. We represent each command as a sub-graph where nodes represent objects mentioned in the command and edges encode relations between nodes described in the command. Then, we use a sub-graph matching algorithm [46] to ensure that the sub-graph representing the command appears only once in the world graph. Sub-graph matching is a NP-hard problem, so we locally optimize our algorithm to have $O(n^2)$ time complexity.

666 D.2 Locally Optimized Sub-graph Matching Algorithm

667 To ensure that there is only one referent target, we make sure that the sub-graph representing the command
 668 only appears once in the graph of the shape world, as illustrated in Figure 6. We include both the complete
 669 matching algorithm, which uses VF2 as the main algorithm (see Alg. 1), and our locally optimized algorithm (see
 670 Alg. 2) for the sub-graph matching problem. Note that this optimized algorithm only applies to three commands
 671 mentioned in Section 4.1, and may need minor modifications to adapt to other commands. We use the VF2
 672 algorithm from the NetworkX package for sub-graph matching.⁶

Algorithm 1 Complete Multi-edge Sub-graph Matching (NP-hard)

Require multi-edge directional graphs G_w for the world and G_c for the command
Require referred object O for the command
Return matching referent targets R

```

1:  $R \leftarrow \{\}$ 
2:  $LiG_w \leftarrow \text{LineGraph}(G_w)$ 
3:  $LiG_c \leftarrow \text{LineGraph}(G_c)$ 
4:  $DiGM \leftarrow \text{VF2}(LiG_w, LiG_c)$ 
5: for  $g_s \leftarrow DiGM.\text{subgraph\_isomorphisms\_iter}()$  do
6:    $isValid \leftarrow \text{True}$ 
7:   for  $pair_w, pair_c \leftarrow g_s.\text{items}()$  do
8:      $rel_w \leftarrow \text{get\_relations}(pair_w)$ 
9:      $rel_c \leftarrow \text{get\_relations}(pair_c)$ 
10:    if not  $rel_w \cap rel_c$  do
11:      break
12:    end for
13:    if  $isValid$  do
14:       $node \leftarrow \text{get\_correspond\_node}(O)$ 
15:       $R \leftarrow R + \{node\}$ 
16:    end for
17: return  $R$ 
```

673 E Models and Experiments Setups

674 For our M-LSTM⁷ and GCN-LSTM⁸ models, we adapt code from the original repositories. For both models, we
 675 optimize for cross-entropy loss using Adam with default parameters [47]. The learning rate starts at $1e^{-4}$ and
 676 decays by 0.9 every 20,000 steps for the M-LSTM model. The learning rate starts at $8e^{-4}$ for the GCN-LSTM
 677 model with the same learning rate decaying schedule. We train for 200,000 steps, with batch size 2000 for
 678 the M-LSTM model, and train for 100 epochs with batch size 200 for the GCN-LSTM model. We choose the best
 679 model during training by the performance on a smaller development set of 2,000 examples, which is consistent
 680 with the training pipeline proposed in Ruis et al. [14] for gSCAN. For M-LSTM, we choose the kernel size for
 681 the CNN to be 7. For GCN-LSTM, we choose the number of message passing iterations to be 4. We adapt the
 682 code released by each paper, which only supports single-GPU training. The training time is about 3 days on a
 683 Standard GeForce RTX 2080 Ti GPU with 11GB memory. To foster reproducibility, we release our adapted
 684 evaluation scripts in our code repository.

685 In generating random splits (Section 6.1), we randomly partition train/dev/test after command–world pairs are
 686 generated. As shown in Table 2, we generate more than 1M example–world pairs in total. Our Simple set is
 687 comparable to gSCAN [14]. However, our Simple set is smaller in size since gSCAN permutes based on agent’s
 688 relative direction against the referent target. Note that for 1-relative-clause and 2-relative-clauses,
 689 we down-sample our commands since we keep world per command approximately the same as gSCAN to ensure
 690 a fair comparison. See Appendix A for detailed dataset statistics. To evaluate our distractor sampling strategies,
 691 we regenerate a new dataset for 2-relative-clauses containing only random distractors and analyze model
 692 performance results. Finally, we combine all three subsets for all patterns and evaluate aggregated performance
 693 (see Table 3 for per pattern performance).

⁶<https://networkx.org/documentation/stable/reference/algorithms/isomorphism.vf2.html>

⁷https://github.com/LauraRuis/multimodal_seq2seq_gSCAN.

⁸https://github.com/HQ01/gSCAN_with_language_conditioned_embedding.

Algorithm 2 Locally Optimized Multi-edge Sub-graph Matching ($O(n^2)$)

```
Require multi-edge directional graphs  $G_w$  for the world and  $G_c$  for the command  
Require referred object 0 for the command  
Return matching referent targets R  
1:  $R \leftarrow \{\}$   
2: for  $n_w \leftarrow G_w.get\_nodes()$  do  
3:    $M \leftarrow \{\}$   
4:    $rel_w \leftarrow n_w.get\_edges()$   
5:    $rel_o \leftarrow G_c.get\_edges(0)$   
6:   if  $|rel_o \cap rel_w| == |rel_o|$  do  
7:     # found a potential candidate, checking nbrs  
8:     for  $nbr \leftarrow n_w.get\_nbrs()$  do  
9:       for  $n_c \leftarrow G_c.get\_nodes()$  where  $n_c \neq 0$  do  
10:         $rel_{nbr} \leftarrow nbr.get\_edges()$   
11:         $rel_c \leftarrow n_c.get\_edges()$   
12:        if  $|rel_{nbr} \cap rel_c| == |rel_c|$  do  
13:          # add nbr in to potential matching list  
14:           $M[n_c] \leftarrow M[n_c] + nbr$   
15:         $isValid \leftarrow \text{True}$   
16:        for  $n_c \leftarrow G_c.get\_nodes()$  where  $n_c \neq 0$  do  
17:          if  $|M[n_c]| == 0$  do  
18:             $isValid \leftarrow \text{False}$   
19:          break  
20:        if  $isValid \ \&\& \text{at\_least\_one\_unique\_for\_each}(M)$  do  
21:           $R \leftarrow R + \{n_w\}$   
22: end for  
23: return R
```

F ReaSCAN Generation Workflow

Figure 6 illustrates our main data generation workflow with an example with a single relational clause. The data generation workflow contains 7 main steps:

- **Step 1:** We first sample a command pattern from the command generator. The command pattern contains the basic structure of the command as in Section 4.1.
- **Step 2:** We fill out the command pattern by supplying its semantics and generate a fully-formed command.
- **Step 3:** Using our simulator, we generate a shape world containing objects conforming to our command as well as distractors. We have four types of distractors, as described in Section 4.2.
- **Step 4:** We then build a graph describing objects and their relations in the shape world generated from the previous step. Using our sub-graph matching algorithm (Appendix D), we validate whether there is only one referent target presented in the shape world grounding the command.
- **Step 5:** If “yes”, we record the command–world pair. If “no”, we fall back to Step 3 and generate a new shape world.

G ReaSCAN Examples

Figure 7 shows more examples for different patterns of commands in ReaSCAN.

H ReaSCAN as an Abstract Reasoning Challenge

Figure 8 shows two simplified examples of how we can transform ReaSCAN into an abstract reasoning challenge following the Abstract Reasoning Corpus proposed by Chollet [48]. Instead of generating the action sequence based on a command–world pair, the task is now defined as predicting the output of a test input world, given multiple pairs of input–output worlds as training examples. This can be seen as a program induction or program synthesis task as well. Our pipeline is able to generate the reasoning logic involved in each task with natural language. This task mimics abstract reasoning tests for humans. To generate reasoning tasks, we first extend our




Figure 6: Data generation workflow with a simplified example.

717 current framework to generate multiple shape worlds for each command along with the position of the referent
 718 targets for each world. Then, we define some primitive actions (e.g., DRAW for changing color; CHANGE for
 719 changing shape) that can be operated on the referent targets. Finally, we generate a new set of shape worlds with
 720 operated referent targets.

721 I Dataset Documentation

722 We have made our dataset and the framework to generate the dataset publicly available at <https://github.com/frankaging/Reason-SCAN>. We bear all responsibility in case of violation of rights. The dataset is
 723 released with Creative Commons Attribution 4.0 International License. Updates and fixes with the dataset can
 724 be found in our code repository. The first release is versioned as ReaSCANv1.0. Any subsequent releases will
 725 have higher version numbers.

727 The dataset and its metadata can be found in the code repository. Additionally, we provide detailed steps
 728 about how to regenerate ReaSCAN in our code repository. Since the data generation framework is novel, it
 729 is self-contained as well. The dataset and its code repository will remain publicly available. We include our
 730 datasheets.




Figure 8: Two simplified abstract reasoning challenges with ReaSCAN. The task mimics human reasoning test where giving a set of input-output (input on the left and output on the right) pairs, the task taker needs to guess the output for the last input. For each task, we provide one potential abstract reasoning to solve the task.

731 **Datasheet for ‘ReaSCAN: Compositional Reasoning in**
732 **Language Grounding’**

733 **A Motivation**

734 **A.1 For what purpose was the dataset created? Was there a specific task in mind? Was**
735 **there a specific gap that needed to be filled? Please provide a description**

736 The dataset was created as a new benchmark for evaluating compositional generalization of neural models by
737 addressing the limitations of gSCAN. We find that gSCAN has three major limitations: (1) its set of instructions is
738 so constrained that compositional interpretation is not required; (2) the distractor objects in its grounded scenarios
739 are mostly not relevant for accurate language understanding; and (3) in many examples, not all modifiers in the
740 command are required for successful navigation, which further erodes the need for compositional interpretation
741 and inflates model performance scores.

742 **A.2 Who created this dataset (e.g., which team, research group) and on behalf of which**
743 **entity (e.g., company, institution, organization)?**

744 The dataset was created by Zhengxuan Wu, Elisa Kreiss, and Christopher Potts at Stanford University, and
745 Desmond C. Ong at National University of Singapore.

746 **A.3 Who funded the creation of the dataset? If there is an associated grant, please provide**
747 **the name of the grantor and the grant name and number**

748 N/A.

749 **B Composition**

750 **B.1 What do the instances that comprise the dataset represent (e.g., documents, photos,**
751 **people, countries)? Are there multiple types of instances (e.g., movies, users, and**
752 **ratings; people and interactions between them; nodes and edges)? Please provide a**
753 **description.**

754 This dataset is a synthetic dataset. Each instance contains:

- 755 1. A command–world pair where the command is a synthetic English sentence and the world is a synthetic
756 $n \times n$ grid-world where we fix $n = 6$, using the open-sourced MiniGym from Open-AI.⁹ The world
757 is represented by a list of objects that are present in the world. Each object is defined by a unique
758 tensor.
- 759 2. An agent initial position and facing direction,
- 760 3. The position of the referent target
- 761 4. The gold label, which is the correct action sequence the agent can execute to reach and operate on the
762 referent target.

763 **B.2 Does the dataset contain all possible instances or is it a sample (not necessarily random)**
764 **of instances from a larger set? If the dataset is a sample, then what is the larger set? Is**
765 **the sample representative of the larger set (e.g., geographic coverage)? If so, please**
766 **describe how this representativeness was validated/verified. If it is not representative of**
767 **the larger set, please describe why not (e.g., to cover a more diverse range of instances,**
768 **because instances were withheld or unavailable).**

769 ReaSCANv1.0 is provided in our project Github repository.¹⁰ It is sampled from a larger set. As our dataset
770 provides a general framework that can scale up to much more examples, it reaches a point where regular
771 computing resources might not be able to train with our dataset. As a result, we randomly sample a subset from
772 our larger pool. We document known potential artifacts from our generation process in Appendix B.

⁹<https://github.com/maximecb/gym-minigrid>

¹⁰<https://github.com/frankaging/Reason-SCAN>

773 **B.3 What data does each instance consist of? “Raw” data (e.g., unprocessed text or**
774 **images)or features? In either case, please provide a description**

775 We provide details about our instances in Section B.1.

776 **B.4 Is there a label or target associated with each instance? If so, please provide a**
777 **description.**

778 The gold label is the correct action sequence in English sentences where each word is separated by “;”. The
779 agent can execute the action sequence to reach and operate on the referent target.

780 **B.5 Is any information missing from individual instances? If so, please provide a**
781 **description, explaining why this information is missing (e.g., because it was unavailable).**
782 **This does not include intentionally removed information, but might include, e.g.,**
783 **redacted text.**

784 Everything is included. No data is missing.

785 **B.6 Are relationships between individual instances made explicit (e.g., users’ movie ratings,**
786 **social network links)? If so, please describe how these relationships are made explicit.**

787 N/A.

788 **B.7 Are there recommended data splits (e.g., training, development/validation, testing)? If**
789 **so, please provide a description of these splits, explaining the rationale behind them.**

790 As our dataset is designed for compositional generalization, we provide train/dev/test splits as well as composi-
791 tional splits in our released dataset. We also provide scripts to generate these splits in our code repository.

792 **B.8 Are there any errors, sources of noise, or redundancies in the dataset? If so, please**
793 **provide a description.**

794 N/A.

795 **B.9 Is the dataset self-contained, or does it link to or otherwise rely on external resources**
796 **(e.g., websites, tweets, other datasets)?**

797 Yes, the dataset is self-contained.

798 **B.10 Does the dataset contain data that might be considered confidential (e.g., data that is**
799 **protected by legal privilege or by doctor/patient confidentiality, data that includes the**
800 **content of individuals non-public communications)? If so, please provide a description.**

801 No, this is a synthetic dataset.

802 **B.11 Does the dataset contain data that, if viewed directly, might be offensive, insulting,**
803 **threatening, or might otherwise cause anxiety? If so, please describe why.**

804 No, this is a synthetic dataset containing synthetic navigation instructions in English and synthetic grid worlds.

805 **B.12 Does the dataset relate to people? If not, you may skip the remaining questions in this**
806 **section.**

807 No, this is a synthetic dataset and does not contain any human label.

808 **B.13 Does the dataset identify any subpopulations (e.g., by age, gender)? If so, please**
809 **describe how these subpopulations are identified and provide a description of their**
810 **respective distributions within the dataset.**

811 N/A.

812 **B.14** Is it possible to identify individuals (i.e., one or more natural persons), either directly
813 or indirectly (i.e., in combination with other data) from the dataset? If so, please
814 describe how.

815 N/A.

816 **B.15** Does the dataset contain data that might be considered sensitive in any way (e.g., data
817 that reveals racial or ethnic origins, sexual orientations, religious beliefs, political
818 opinions or union memberships, or locations; financial or health data; biometric or
819 genetic data; forms of government identification, such as social security numbers;
820 criminal history)?

821 N/A.

822 **C Collection Process**

823 N/A. This is a synthetic dataset containing synthetic navigation instructions in English and synthetic grid worlds.
824 As a result, we do not collect any human data.

825 **D Preprocessing/cleaning/labeling**

826 **D.1** Was any preprocessing/cleaning/labeling of the data done (e.g., discretization or
827 bucketing, tokenization, part-of-speech tagging, SIFT feature extraction, removal of
828 instances, processing of missing values)? If so, please provide a description. If not, you
829 may skip the remainder of the questions in this section.

830 No, the synthetic dataset is provided as-is.

831 **D.2** Was the “raw” data saved in addition to the preprocessed/cleaned/labeled data (e.g., to
832 support unanticipated future uses)? If so, please provide a link or other access point to
833 the “raw” data.

834 N/A.

835 **D.3** Is the software used to preprocess/clean/label the instances available? If so, please
836 provide a link or other access point

837 N/A.

838 **E Use**

839 **E.1** Has the dataset been used for any tasks already? If so, please provide a description.

840 No, this is our first release of the dataset.

841 **E.2** Is there a repository that links to any or all papers or systems that use the dataset? If so,
842 please provide a link or other access point.

843 No, this is our first release of the dataset.

844 **E.3** What (other) tasks could the dataset be used for?

845 This dataset is designed for evaluating compositional generalization of neural models as a synthetic navigation
846 task. This task can be used for referring expression resolution as well.

847 **E.4 Is there anything about the composition of the dataset or the way it was collected and**
848 **preprocessed/cleaned/labeled that might impact future uses? For example, is there**
849 **anything that a future user might need to know to avoid uses that could result in unfair**
850 **treatment of individuals or groups (e.g., stereotyping, quality of service issues) or other**
851 **undesirable harms (e.g., financial harms, legal risks) If so, please provide a description.**
852 **Is there anything a future user could do to mitigate these undesirable harms?**

853 There is minimal risk for harm: this is a synthetic dataset and does not contain any human label.

854 **E.5 Are there tasks for which the dataset should not be used? If so, please provide a**
855 **description.**

856 No, this dataset is used for training neural models that solve the synthetic task posed by the dataset only. The
857 dataset should not be used for any real-world applications.

858 **F Distribution**

859 **F.1 Will the dataset be distributed to third parties outside of the entity (e.g., company,**
860 **institution, organization) on behalf of which the dataset was created? If so, please**
861 **provide a description.**

862 Yes, the dataset is publicly available on the internet.

863 **F.2 How will the dataset will be distributed (e.g., tarball on website, API, GitHub)? Does the**
864 **dataset have a digital object identifier (DOI)?**

865 The dataset is publicly available at our Github repository.

866 **F.3 When will the dataset be distributed?**

867 The dataset is first released in 2021.

868 **F.4 Will the dataset be distributed under a copyright or other intellectual property (IP)**
869 **license, and/or under applicable terms of use (ToU)? If so, please describe this license**
870 **and/or ToU, and provide a link or other access point to, or otherwise reproduce, any**
871 **relevant licensing terms or ToU, as well as any fees associated with these restrictions.**

872 Our dataset has a Creative Commons Attribution 4.0 International License. The dataset is publicly available on
873 the internet. People are allowed to use our scripts to generate their own version of ReaSCAN as well.

874 **F.5 Do any export controls or other regulatory restrictions apply to the dataset or to**
875 **individual instances? If so, please describe these restrictions, and provide a link or other**
876 **access point to, or otherwise reproduce, any supporting documentation.**

877 Unknown.

878 **G Maintenance**

879 **G.1 Who is supporting/hosting/maintaining the dataset?**

880 Zhengxuan Wu is supporting/maintaining the dataset.

881 **G.2 How can the owner/curator/manager of the dataset be contacted (e.g., email address)?**

882 wuzhengx@stanford.edu.

883 **G.3 Is there an erratum? If so, please provide a link or other access point.**

884 There is not an explicit erratum, but updates and fixes with the dataset can be found in our Github repository.
885 The first release is versioned as ReaSCANv1.0. Any subsequent releases will have higher version numbers.

886 **G.4 Will the dataset be updated (e.g., to correct labeling errors, add new instances, delete**
887 **instances)? If so, please describe how often, by whom, and how updates will be**
888 **communicated to users (e.g., mailing list, GitHub)?**

889 This will be posted on the dataset Github repository.

890 **G.5 If the dataset relates to people, are there applicable limits on the retention of the data**
891 **associated with the instances (e.g., were individuals in question told that their data**
892 **would be retained for a fixed period of time and then deleted)? If so, please describe**
893 **these limits and explain how they will be enforced.**

894 N/A.

895 **G.6 Will older versions of the dataset continue to be supported/hosted/maintained? If so,**
896 **please describe how. If not, please describe how its obsolescence will be communicated**
897 **to users.**

898 N/A.

899 **G.7 If others want to extend/augment/build on/contribute to the dataset, is there a**
900 **mechanism for them to do so? If so, please provide a description. Will these**
901 **contributions be validated/verified? If so, please describe how. If not, why not? Is there**
902 **a process for communicating/distributing these contributions to other users? If so,**
903 **please provide a description.**

904 Others may do so and should contact the original authors about incorporating fixes/extensions.